



**IDEMITSU**

# SAFETY DATA SHEET

<b>Product Name:</b>	<b>PPE</b>			
Nissan Genuine CVT Fluid NS-3, 12 x 1 Liter Case				

Revision Date: 04-Feb-2019

Revision Number: 3

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

**Product Name:**

Nissan Genuine CVT Fluid NS-3, 12 x 1 Liter Case

#### Other means of identification

**Product Code:**

34015005-71200C020

### 1.2 Recommended use of the chemical and restrictions on use

**Recommended Use:**

Automotive Lubricant

### 1.3 Details of the supplier of the safety data sheet

**Manufactured by:**

Idemitsu Lubricants America Corporation  
701 Port Rd., Jeffersonville, IN. 47130  
Email: sds@ilacorp.com

**24 Hour Emergency Phone Number:**

Within USA and Canada: 1 800-424-9300  
Outside USA and Canada: + 1 703-741-5970  
(collect calls accepted)

34015005-71200C020 - Nissan Genuine CVT Fluid  
NS-3, 12 x 1 Liter Case

Revision Date: 04-Feb-2019

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification

This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS 2015.

Skin sensitization	Category 1
--------------------	------------

### Label elements



**Signal word**

**Warning**

#### Hazard Statements

H317 - May cause an allergic skin reaction

#### Precautionary Statements - Prevention:

P261 - Avoid breathing dust, fume, gas, mist, vapors, or spray.  
P280 - Wear protective gloves. P272 - Contaminated work clothing should not be allowed out of the workplace.

#### Precautionary Statements - Response

P362 + P364 - Take off all contaminated clothing and wash it before reuse.

#### Skin

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.  
P363 - Wash contaminated clothing before reuse. P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.

#### Precautionary Statements - Disposal:

P501 - Dispose of contents/ container to an approved waste disposal plant.

#### Hazards not otherwise classified (HNOC)

Not applicable

### 2.3 Other information

#### Other hazards

May be harmful if swallowed  
May be harmful in contact with skin  
Harmful to aquatic life

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Not applicable

### 3.2 Mixture

#### Hazardous Components

Chemical name	CAS No.	Weight-%	US GHS Classification	Notes
Long chain alkyl amine alkylene	64051-50-9	<1	Skin Sens. 1 (H317)	

34015005-71200C020 - Nissan Genuine CVT Fluid  
NS-3, 12 x 1 Liter Case

Revision Date: 04-Feb-2019

amine			
-------	--	--	--

**Non-Hazardous Components**

Chemical name	CAS No.	Weight-%
Lubricating Base Stocks	Mixture	70-80
Synthetic Lubricant	Mixture	5-10

**4. FIRST AID MEASURES**

**4.1 First Aid Measures**

**General Advice**

If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for medical treatment.

**Eye Contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists: Get medical advice or attention.

**Skin Contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before re-use. Call a physician immediately.

**Inhalation**

Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician immediately.

**Ingestion**

Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty lean forward to reduce the risk of aspiration. If symptoms persist, call a physician.

**Protection of First-aiders**

Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**4.2 Most important symptoms and effects, both acute and delayed**

**Symptoms**

No Information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Notes to Physician**

Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

**Flammable Properties**

NFPA: Class IIIB Combustible Liquid

**5.1 Suitable Extinguishing Media:**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment

**Unsuitable Extinguishing Media:**

Do not use a solid water stream as it may scatter and spread fire.

**5.2 Specific Hazards Arising from the Chemical**

Keep product and empty container away from heat and sources of ignition.

**Hazardous combustion products**

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and are not limited to:  
Carbon oxides  
Calcium Oxides (CaOx)  
Nitrogen oxides (NOx)  
Oxides of Phosphorus  
Sulphur oxides

### 5.3 Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

#### **Personal precautions**

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of ignition.

### 6.2. Environmental precautions

#### **Environmental Precautions**

See section 12 for additional ecological information. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow into any sewer, on the ground or into any body of water. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

### Methods and material for containment and cleaning up

#### **Methods for Clean-up**

Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### Spill Management

#### **LARGE SPILLS**

Eliminate sources of ignition. Prevent additional discharge of material if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify the National Response Center.

#### **WATER SPILLS**

Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

## 7. HANDLING AND STORAGE

### 7.1. Precautions for safe handling

#### **Handling**

Do not breathe dusts or mists. Avoid contact with eyes, skin and clothing. Use personal protection recommended in Section 8. Wear protective gloves, protective clothing, eye protection, and face protection. Wash hands thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Should not be released into the environment.

#### **Safe Handling Advice**

Handle in accordance with good industrial hygiene and safety practices. Take precautionary measures against static discharges.

### 7.2. Conditions for safe storage, including any incompatibilities

#### **Storage**

Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place.

34015005-71200C020 - Nissan Genuine CVT Fluid  
NS-3, 12 x 1 Liter Case

Revision Date: 04-Feb-2019

Technical measures/Precautions

Ensure adequate ventilation.

Incompatible Materials and/or Coatings

No Information available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control Parameters

#### Exposure Guidelines

Chemical name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>		TWA 5 mg/m <sup>3</sup> ST 10 mg/m <sup>3</sup>			

### 8.2 Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

#### Personal Protective Equipment

##### Eye/face protection

Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If splashes are likely to occur wear tight fitting safety goggles and/or face-shield.

##### Skin protection

Wear protective gloves/clothing. Long sleeved clothing. Choose the appropriate protective clothing and gloves based on the tasks being performed to avoid exposed skin surfaces.  
**Glove Type:** Neoprene, Nitriles

##### Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### General Hygiene Considerations

When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Dark Green Blue / Opaque
Physical state	Liquid
Odor	Characteristic
Odor Threshold	No Information available
pH	Not applicable
Melting point / melting range	Not applicable
Boiling point / boiling range	No Information available

Flash Point	> 170 °C / 338 °F COC ASTM D92
Evaporation Rate	No Information available
Flammability Limit in Air	No Information available
Explosion Limits	No Information available
Vapor pressure @20 °C (kPa)	No Information available
Vapor density	No Information available
Density	0.85 g/cm <sup>3</sup> @15°C
Solubility(ies)	No Information available
Partition coefficient	No Information available
Autoignition Temperature	No Information available
Decomposing Temperature	No Information available
Kinematic viscosity	@ 40C = 25.81 cSt; @ 100C = 6.23 cSt

#### Other Information

DMSO extract by IP346

Less than 3.0 wt% (mineral oil component only)

### 10. STABILITY AND REACTIVITY

#### 10.1 Reactivity

Reactivity:

The product is chemically stable.

#### 10.2 Chemical stability

Chemical Stability

Stable under normal conditions.

#### Possibility of hazardous reactions

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

#### 10.4 Conditions to avoid

Conditions to Avoid

Heat, flames and sparks.

#### 10.5 Incompatible materials

Incompatible Materials

Strong oxidizing agents

#### 10.6 Hazardous Decomposition Products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

### 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on likely routes of exposure

Inhalation

May cause irritation of respiratory tract.

Eye contact

May cause slight irritation.

Skin Contact

May cause an allergic skin reaction.

Ingestion

May be harmful if swallowed.

### 11.2 Information on toxicological effects

**Symptoms** No Information available

### 11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Not classified.  
**Serious eye damage/eye irritation** Not classified.  
**Sensitization** May cause an allergic skin reaction.  
**Mutagenic effects** Not classified.

### 11.4 Carcinogenicity

**Carcinogenicity:** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH.

**Legend:** *NTP (National Toxicology Program), IARC (International Agency for Research on Cancer), OSHA (Occupational Safety and Health Administration of the US Department of Labor), ACGIH (American Conference of Governmental Industrial Hygienists)*

**Reproductive toxicity** Not classified.  
**Reproductive Effects** Not classified.  
**STOT - single exposure** Not classified  
**STOT - repeated exposure** Not classified  
**Target organ effects** Not classified.  
**Aspiration hazard** Not classified.

### 11.5 Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

#### Product Information (Estimated):

**ATEmix (oral)** > 4,000 mg/kg  
**ATEmix (dermal)** > 2,000 mg/kg  
**ATEmix (inhalation-dust/mist)** > 5 mg/l

## 12. ECOLOGICAL INFORMATION

### 12.1 Ecotoxicity

**Ecotoxicity effects** Harmful to aquatic life. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

**Unknown aquatic toxicity** 10.13 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

**12.2 Persistence and degradability**

No Information available.

**12.3 Bioaccumulation/Accumulation**

No Information available.

**12.4 Mobility in Environmental Media**

No Information available.

**12.5 Other adverse effects:**

No Information available.

**PBT and vPvB assessment**

No Information available

**13. DISPOSAL CONSIDERATIONS**

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

**Waste Disposal Method**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

**Contaminated packaging**

Dispose of in accordance with local regulations.

**14. TRANSPORT INFORMATION**

**DOT**

Not regulated

**DOT - Bulk**

Not regulated

**IATA**

Not regulated

**IMDG**

Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**

<b>TSCA</b>	All ingredients are on the inventory or exempt from listing
<b>DSL</b>	All ingredients are on the inventory or exempt from listing
<b>Chemical name</b>	<b>NDSL</b> <b>CAS No.</b> <b>Weight-%</b>
Alkyl Phosphites	X AAC 151872 <1
Phenol, (tetrapropenyl) derivatives	X 74499-35-7 <0.1
<b>ENCS</b>	All ingredients are on the inventory or exempt from listing
<b>IECSC</b>	All ingredients are on the inventory or exempt from listing
<b>KECL</b>	All ingredients are on the inventory or exempt from listing
<b>PICCS</b>	All ingredients are on the inventory or exempt from listing
<b>AICS</b>	All ingredients are on the inventory or exempt from listing
<b>REACH</b>	All ingredients are on the inventory or exempt from listing

**USA**



**Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazardous Categorization**

<b>Acute health hazard</b>	Skin Sensitizer
<b>Chronic Health Hazard</b>	Skin Sensitizer
<b>Fire hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**CERCLA/SARA 302 & 304**

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical name	CAS No.	Weight-%	RQ	TPQ
Methyl methacrylate	80-62-6	<0.1	RQ 1000lb final RQ RQ 454kg final RQ	
Alkyl alcohol	107-21-1	<0.01	RQ 5000lb final RQ RQ 2270kg final RQ	

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

Chemical name	CAS No.	Weight-%	HAPS data
Methyl methacrylate	80-62-6	<0.1	X
Alkyl alcohol	107-21-1	<0.01	X

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CAS No.	Weight-%	U.S. - CWA (Clean Water Act)
Methyl methacrylate	80-62-6	<0.1	X

**State Regulations**

**California Proposition 65**

Label:



**WARNING.** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Chemical name	CAS No.	Weight-%	California Prop. 65	Maximum Allowable Dose for Reproductive Toxicity (MADLS)	Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Alkyl alcohol	107-21-1	<0.01	Developmental	8700µg/dayoral;ingested	

**State Right-to-Know**

**34015005-71200C020 - Nissan Genuine CVT Fluid  
NS-3, 12 x 1 Liter Case**

**Revision Date:** 04-Feb-2019

Chemical name	CAS No.	Weight-%	New Jersey
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	50-60	X
Reaction product, amines, polyethylenepoly- w/ succinic anhydride, polyisobutenyl derivatives, borated	134758-95-5	1-5	X
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	1-5	X

Chemical name	CAS No.	Weight-%	Massachusetts
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	50-60	X

Chemical name	CAS No.	Weight-%	Pennsylvania
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	50-60	X
Reaction product, amines, polyethylenepoly- w/ succinic anhydride, polyisobutenyl derivatives, borated	134758-95-5	1-5	X
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	1-5	X

**New Jersey Worker and Community Right-to-Know Act:**

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows:  
PETROLEUM OIL (Lubricating Oil)

**Canada**

This material has been classified in accordance with the WHMIS 2015 regulation

Chemical name	CAS No.	Weight-%	NPRI
White mineral oil	8042-47-5	<1	Listed
Methyl methacrylate	80-62-6	<0.1	Listed

**Legend**

NPRI - National Pollutant Release Inventory

**16. OTHER INFORMATION**

**NFPA** Health hazards: 2 Flammability: 1 Instability: 0



**Prepared By:** Lindsay Lindsey

**Revision Date:** 04-Feb-2019

**Revision Summary:** Update vendor GHS Classification information

**Disclaimer:**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**